


A modern, high-performing downlight suitable for commercial applications. Die cast aluminium body with a high efficiency reflector and clear polycarbonate lens. High quality LED technology ensures the luminaire's long life while maintaining colour quality.



Black



Bright silver



Matt silver



Gold


CODE GENERATION

| | LUMINAIRE | POWER | CCT | OPTIC | REFLECTOR | COLOUR | DIMMING |
|--------------|-----------|-------|-------|-------|-----------|--------|---------|
| CODE | LN-1001 | 20 | W30 | 60 | B | W | D |
| REQUIREMENTS | LAINIEY 4 | 20W | 3000K | 60° | BLACK | WHITE | DALI |

COMPLETE CODE = LN-1001-20-W30-60-B-W-D

LUMINAIRE OPTIONS

| POWER | CODE | CCT | CODE | OPTIC | CODE | REFLECTOR | CODE | COLOUR | CODE | DIMMING | CODE |
|-------|------|-------|------|-------|------|---------------|------|--------|------|---------------|------|
| 20W | 20 | 2700K | W27 | 24° | 24 | BLACK | B | WHITE | W | NON-DIM | N |
| 25W | 25 | 3000K | W30 | 38° | 38 | BRIGHT SILVER | BS | BLACK | B | TRAILING EDGE | T |
| | | 4000K | W40 | 60° | 60 | MATT SILVER | MS | CUSTOM | C | 1-10V | A |
| | | | | | | GOLD | G | | | DALI | D |
| | | | | | | | | | | CASAMBI | C |



| MECHANICAL | |
|--------------------|---------------------|
| Installation | Recessed |
| Housing Material | Aluminium |
| Lens Material | Clear Polycarbonate |
| Ingress Protection | IP54 (Below) |
| Luminaire Diameter | 118mm |
| Cut-Out Diameter | 100mm |
| Luminaire Depth | 82.5mm |

| ELECTRICAL | |
|-----------------|---------|
| Driver Included | Yes |
| Voltage Input | 230V AC |

| LIGHT SOURCE | |
|------------------------|-------------------|
| LED Manufacturer | Bridgelux |
| Beam Angle | 24-60° |
| Colour Rendition (CRI) | Ra 90 |
| Colour Consistency | SDCM 3 |
| Lifetime | L90 B10 60,000hrs |

| LUMEN OUTPUT | | |
|--------------|-----------|--------|
| 20W | 24° 3000K | 1876lm |
| 20W | 38° 3000K | 1861lm |
| 20W | 60° 3000K | 1900lm |
| 25W | 24° 3000K | 2211lm |
| 25W | 38° 3000K | 2185lm |
| 25W | 60° 3000K | 2581lm |

