


A modern, high-performing downlight suitable for commercial applications. Die cast aluminium body with a high efficiency reflector and clear polycarbonate lens. High quality LED technology ensures the luminaire's long life while maintaining colour quality.



Black



Bright silver



Matt silver



Gold


CODE GENERATION

	LUMINAIRE	POWER	CCT	OPTIC	REFLECTOR	COLOUR	DIMMING
CODE	LN-1254	30	W30	60	B	W	D
REQUIREMENTS	LAINÉY 4	30W	3000K	60°	BLACK	WHITE	DALI

COMPLETE CODE = LN-1254-30-W30-60-B-W-D

LUMINAIRE OPTIONS

POWER	CODE	CCT	CODE	OPTIC	CODE	REFLECTOR	CODE	COLOUR	CODE	DIMMING	CODE
30W	30	2700K	W27	24°	24	BLACK	B	WHITE	W	NON-DIM	N
35W	35	3000K	W30	38°	38	BRIGHT SILVER	BS	BLACK	B	TRAILING EDGE	T
		4000K	W40	60°	60	MATT SILVER	MS	CUSTOM	C	1-10V	A
						GOLD	G			DALI	D
										CASAMBI	C



MECHANICAL

Installation	Recessed
Housing Material	Aluminium
Lens Material	Clear Polycarbonate
Ingress Protection	IP54 (Below)
Luminaire Diameter	143mm
Cut-Out Diameter	125mm
Luminaire Depth	90mm

ELECTRICAL

Driver Included	Yes
Voltage Input	230V AC

LIGHT SOURCE

LED Manufacturer	Bridgelux
Beam Angle	24-60°
Colour Rendition (CRI)	Ra 90
Colour Consistency	SDCM 3
Lifetime	L90 B10 60,000hrs

LUMEN OUTPUT

30W	24° 4000K	3045lm
30W	38° 4000K	3084lm
30W	60° 4000K	3066lm
35W	24° 4000K	3397lm
35W	38° 4000K	3432lm
35W	60° 4000K	3431lm

