


A modern, high-performing downlight suitable for commercial applications. Die cast aluminium body with a high efficiency reflector and clear polycarbonate lens. High quality LED technology ensures the luminaire's long life while maintaining colour quality.



Black



Bright silver



Matt silver



Gold

## CODE GENERATION

	LUMINAIRE	POWER	CCT	OPTIC	REFLECTOR	COLOUR	DIMMING
CODE	LN-1507	40	W30	50	B	W	D
REQUIREMENTS	LAINY 7	40W	3000K	50°	BLACK	WHITE	DALI

COMPLETE CODE = LN-1507-40-W30-50-B-W-D

## LUMINAIRE OPTIONS

POWER	CODE	CCT	CODE	OPTIC	CODE	REFLECTOR	CODE	COLOUR	CODE	DIMMING	CODE
20W	20	2700K	W27	24°	24	BLACK	B	WHITE	W	NON-DIM	N
25W	25	3000K	W30	38°	38	BRIGHT SILVER	BS	BLACK	B	TRAILING EDGE	T
		4000K	W40	60°	60	MATT SILVER	MS	CUSTOM	C	1-10V	A
										DALI	D
						GOLD	G			CASAMBI	C

MECHANICAL	
Installation	Recessed
Housing Material	Aluminium
Lens Material	Clear Polycarbonate
Ingress Protection	IP54 (Below)
Luminaire Diameter	168mm
Cut-Out Diameter	150mm
Luminaire Depth	110mm

ELECTRICAL	
Driver Included	Yes
Voltage Input	230V AC

LIGHT SOURCE	
LED Manufacturer	Bridgelux
Beam Angle	24-50°
Colour Rendition (CRI)	Ra 90
Colour Consistency	SDCM 3
Lifetime	L90 B10 60,000hrs

LUMEN OUTPUT		
40W	24° 4000K	3632lm
40W	38° 4000K	3630lm
40W	50° 4000K	3713lm
45W	24° 4000K	4258lm
45W	38° 4000K	4259lm
45W	50° 4000K	4740lm

