

KIOS 7 (KI-60578)**Product description**

With recessing box / driver - Flat frame - RGBW

**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- 5.5 mm thick front ring in grade 316 stainless steel
- Single cable entry, through wiring upon request
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency PMMA lens
- Integral control gear
- Recessing box in high-density polyethylene is included
- Suitable for drive-over with a maximum load of 2000 kg
- Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 50 km/h
- Load is transferred by the housing to the foundation
- The distance between the luminaire and the illuminated surface should be at least 0.5 m



Optic**Product colour**

KIOS 7 (KI-60578)

Technical information

Material	Stainless Steel	Input voltage	220-240 V 50/60 Hz	Dimming type	DMX, DMX/RDM
Light source	7 LED	Optic	N, M, E	Product colours	Stainless Steel
Power	29 W	Optic value	21°, 35°, 26°x48°	Weight	6.5 kg
Lumen	1063 - 1299 lm	CCT / CRI	RGBW30, RGBW40	Operating temperature	-20 °C to 40 °C
Efficacy	37 - 45 lm/W	Bug	B0-U5-G0	Through wiring	Single cable entry, through wiring upon request
Driver option	Integral control gear	ULR	100%	Lens / Reflector / Optic	Clear toughened glass, High-efficiency PMMA lens
Driver	Constant current (CC)	ULOR	100%		

KI-60578



Accessories



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM