



A modern, high-performing downlight suitable for commercial and residential applications. Die cast aluminium body with a high efficiency reflector and clear polycarbonate lens. High quality LED technology ensures the luminaire's long life while maintaining colour quality.



MECHANICAL

Installation	Recessed
Housing Material	Aluminium
Lens Material	Clear Polycarbonate
Ingress Protection	IP65 (Below)
Luminaire Diameter	105mm
Cut-Out Diameter	98mm
Luminaire Depth	68mm

ELECTRICAL

Driver Included	Yes
Voltage Input	230V AC

LIGHT SOURCE

LED Manufacturer	Cree
LED Series	CMU
Beam Angle	60°
Colour Rendition (CRI)	Ra 92
Colour Consistency	SDCM 2
Lifetime	L90 B10 60,000hrs

LUMEN OUTPUT

10W	3000K	998lm
10W	4000K	1051lm
13W	3000K	1116lm
13W	4000K	1175lm
15W	3000K	1361lm
15W	4000K	1433lm



LUMINAIRE OPTIONS

POWER	CODE	CCT	CODE	COLOUR	CODE	DIMMING	CODE
10W	10	2700K	W27	WHITE	W	TRAILING EDGE	T
13W	13	3000K	W30	BLACK	B	1-10V	A
15W	15	4000K	W40	CUSTOM	C	DALI	D
						CASAMBI	C

CODE GENERATION

	LUMINAIRE	POWER	CCT	COLOUR	DIMMING
CODE	HR-1013	15	W30	W	T
REQUIRMENTS	HUNTER 105MM	15W	3000K	WHITE	TRAILING EDGE

COMPLETE CODE = HR-1013-15-W30-W-T