


A modern, high-performing Track mounted spot light suitable for commercial, retail and residential applications. Extruded aluminium body with a high efficiency clear polycarbonate lens. High quality LED technology ensures the luminaire's long life while maintaining colour quality.



MECHANICAL	
Installation	3-Circuit Track
Housing Material	Aluminium
Lens Material	PMMA Lens
Ingress Protection	IP20
Luminaire Rotate	355°
Luminaire Tilt	95°

ELECTRICAL	
Driver Included	Yes
Voltage Input	230V AC

LIGHT SOURCE	
LED Manufacturer	Bridgelux
Beam Angle	12°, 24°, 36° or 60°
Luminaire Power	10-20W
Colour Rendition (CRI)	Ra 90
Colour Consistency	SDCM 3
Lifetime	L90 B10 60,000hrs



## CODE GENERATION

	LUMINAIRE	POWER	OPTIC	CCT	COLOUR	DIMMING
CODE	LA-TS	15	60	W30	B	T
REQUIREMENTS	LUKA	15W	60°	3000K	BLACK	TRAILING EDGE

**COMPLETE CODE = LA-TS-15-60-W30-B-T**

## LUMINAIRE OPTIONS

POWER	CODE	OPTIC	CODE	CCT	CODE	COLOUR	CODE	DIMMING	CODE
10W	10	12°	12	2700K	W27	WHITE	W	TRAILING EDGE	T
15W	15	24°	24	3000K	W30	BLACK	B	DALI*	D
		36°	36	4000K	W40	CUSTOM*	C	CASAMBI*	C
		60°	60						

## ACCESSORIES

ACCESSORY	CODE
HONEY COMB	LAF-60-01
CROSS LOUVRE	LAF-60-02
SNOOT	LAF-60-03
EYE SNOOT	LAF-60-04
WALL WASH RING	LAF-60-05
BARN DOOR	LAF-60-06

\* TRACK ADAPTOR COLOUR NOT CUSTOMIZABLE, ONLY AVAILABLE IN BLACK, WHITE & GREY  
 \* DALI DRIVER IS BUILT INTO TRACK ADAPTER, 6-WIRE TRACK ONLY  
 \* CASAMBI DRIVER IS BUILT INTO TRACK ADAPTER, 4-WIRE TRACK ONLY



LAF-60-01



LAF-60-02



LAF-60-03



LAF-60-04



LAF-60-05



LAF-60-06

### 10W FIXED OPTIC

12°	3000K	964lm
12°	4000K	1012lm
24°	3000K	962lm
24°	4000K	1010lm
36°	3000K	1063lm
36°	4000K	1116lm
60°	3000K	976lm
60°	4000K	1025lm

### 15W FIXED OPTIC

12°	3000K	1519lm
12°	4000K	1595lm
24°	3000K	1426lm
24°	4000K	1497lm
36°	3000K	1377lm
36°	4000K	1445lm
60°	3000K	1375lm
60°	4000K	1443lm