


A modern, high-performing Track mounted spot light suitable for commercial, retail and residential applications. Extruded aluminium body with a high efficiency clear polycarbonate lens. High quality LED technology ensures the luminaire's long life while maintaining colour quality.



CODE GENERATION

	LUMINAIRE	POWER	OPTIC	CCT	COLOUR	DIMMING
CODE	LA-TS	15	60	W30	B	T
REQUIREMENTS	LUKA	15W	60°	3000K	BLACK	TRAILING EDGE

COMPLETE CODE = LA-TS-15-60-W30-B-T

LUMINAIRE OPTIONS

POWER	CODE	OPTIC	CODE	CCT	CODE	COLOUR	CODE	DIMMING	CODE
10W	10	6°	6	2700K	W27	WHITE	W	TRAILING EDGE	T
15W	15	12°	12	3000K	W30	BLACK	B	DALI*	D
		24°	24	4000K	W40	CUSTOM*	C	CASAMBI*	C
		36°	36					ONBOARD	OBD
		60°	60						

* TRACK ADAPTOR COLOUR NOT CUSTOMIZABLE, ONLY AVAILABLE IN BLACK, WHITE & GREY
* DALI DRIVER IS BUILT INTO TRACK ADAPTER, 6-WIRE TRACK ONLY
* CASAMBI DRIVER IS BUILT INTO TRACK ADAPTER, 4-WIRE TRACK ONLY

MECHANICAL

Installation	3-Circuit Track
Housing Material	Aluminium
Lens Material	PMMA Lens
Ingress Protection	IP20
Luminaire Rotate	355°
Luminaire Tilt	95°

ELECTRICAL

Driver Included	Yes
Voltage Input	230V AC

LIGHT SOURCE

LED Manufacturer	Bridgelux
Beam Angle	6°, 12°, 24°, 36°, 60°
Luminaire Power	10-15W
Colour Rendition (CRI)	Ra 90
Colour Consistency	SDCM 3
Lifetime	L90 B10 60,000hrs



OPTIONAL ONBOARD DIMMER



ACCESSORIES

ACCESSORY	CODE
HONEY COMB	LAF-60-01
CROSS LOUVRE	LAF-60-02
SNOOT	LAF-60-03
EYE SNOOT	LAF-60-04
WALL WASH RING	LAF-60-05
BARN DOOR	LAF-60-06

SNOOT ACCESSORIES

*NOT SUITABLE FOR 6" VERSION



LAF-60-01



LAF-60-02



LAF-60-03



LAF-60-04




LAF-60-05



LAF-60-06

FILTER LENSES - 6° BEAM ANGLE ONLY



CIRCULAR SMALL
LAF-6-CS




SQUARE SMALL
LAF-6-SS




RECTANGULAR
LAF-6-R



MIDDLE LINE
LAF-6-ML



CIRCULAR BIG
LAF-6-CB



SQUARE BIG
LAF-6-SB



NARROW LINE
LAF-6-NL



WIDE LINE
LAF-6-WL

10W FIXED OPTIC

6°	3000K	426lm
6°	4000K	455lm
12°	3000K	964lm
12°	4000K	1012lm
24°	3000K	962lm
24°	4000K	1010lm
36°	3000K	1063lm
36°	4000K	1116lm
60°	3000K	976lm
60°	4000K	1025lm

15W FIXED OPTIC

12°	3000K	1519lm
12°	4000K	1595lm
24°	3000K	1426lm
24°	4000K	1497lm
36°	3000K	1377lm
36°	4000K	1445lm
60°	3000K	1375lm
60°	4000K	1443lm